




## FAN FORCED OVEN



<b>Colour:</b>	White	Stainless Steel
<b>Model:</b>	IOF6WE1	IOF6SE2
<b>Dimensions:</b>	597mm(H) x 595mm(W) x 540mm(D)	
<b>Cut Out Size:</b>	570mm(H) x 560mm(W) x 550mm(D)	
<b>Packaging:</b>	<i>Carton Size</i>	66cm(H) x 66cm(W) x 68cm(D)
	<i>Carton Cubic metres</i>	0.296 cubic metres
	<i>Carton Weight</i>	33 kg
<b>Oven Capacity:</b>	53 litres	
<b>Function Selector Knob:</b>	<ul style="list-style-type: none"> <li>• Light off</li> <li> Oven light on</li> <li> Fan on (defrost)</li> <li>Rear heating element and fan on (fan forced)</li> <li> Grill heating element on</li> </ul>	
<b>Method of Installation:</b>	Wall mounted or under bench	
<b>Total Kilowatts:</b>	2350kW	
<b>Maximum Amperage:</b>	9.8 amps. Recommended to use a 15amp connection	
<b>Electrical Connection:</b>	Hard wired, single phase	

Description	Nominal Data
Rear heating element of the oven	2000W
Grill element	1800W
Oven light bulb	15W - E 14 - T300
Cooling fan	18..22 W
Fan for rear heating element	25..29 W
Supply cable	H05 RR - F 3 x 1.5mm <sup>2</sup> cross section

## FAN FORCED OVEN

<b>Temperature Selection:</b>	75° to 225° Celsius
<b>Ventilation:</b>	Front vented
<b>Cooling Fan:</b>	Tangential safety cooling fan to reduce the temperature of oven surrounds
<b>Timer Knob:</b>	Manual timer up to 60 minutes. Timer will ring when the set time has elapsed
<b>Tray Configuration:</b>	Oven shelf rack, grill rack, drip tray, grill pan handle
<b>Method of Installation:</b>	The oven can be fitted into a tall cabinet or a base module but to reduce the risk of the oven overheating there must be adequate supply of airflow, therefore provision must be made within the cabinetry for effective air circulation.

To make sure the appliance is properly aerated remove the rear panel of the base module or make a hole (A) as shown in figure.

Put the appliance in place and secure with the screws provided.

The oven must be supported by a base that will withstand its full weight. Screws are only used to locate the appliance inside its cabinet housing.

**Warning:** IAG Appliances have been tested and approved to the relevant Australian Standards. However if an oven is built into or close to cabinetry, the cabinetry must be able to withstand temperatures of 75° Celsius. Failure to do so may result in deterioration or discolouring of the cabinetry. This warning is particularly relevant where vinyl coated products are installed. In this instance oven heat deflectors should be used. IAG Appliances cannot accept responsibility for damage caused where the cabinetry fails to meet the above temperature tolerance requirements.

