

CERAMIC 900MM



- Colour:** Ceramic glass
Stainless Steel Trim
Black Knobs
- Model:** ICC9SE1
- Dimensions:** 900mm (L) x 510mm (W) x 48mm (D)
- Cut Cut Size:** 880mm (L) x 490mm (W) x 48mm (D)
- Packaging:** Carton Size 980mm (L) x 575mm (W) x 125mm (D)
Carton Cubic metres 0.070 cubic metres
Carton Weight 12.5kg
- Electrical Connection:** Supply lead not supplied. Connection box at centre underside of cooktop.

Elements	Plate Type	Element Rating (W)	Element Diameter
Front left	Highlight Rapid Heat	1200	145
Front right	Highlight Rapid Heat	1700 / 700	180 / 120
Rear left	Highlight Rapid Heat	2200 / 1400	265 / 170
Rear middle	Highlight Rapid Heat	1800	180
Rear right	Highlight Rapid Heat	1200	145

- Other:**
- 240 Volts ~ 50Hz
 - 25 amps
 - Must be hard wired
 - 5 residual heat safety warning lights
 - Graduated temperature controls 1-9

CERAMIC 900MM

Method of Operation:

- Use the control knobs to set the desired temperature. Turn them clockwise for maximum heat.
- In the case of plates with a double area, the external heating element can be switched on starting from zero and turning in an anticlockwise direction

Method of Installation:

- Cut benchtop to dimensions as shown
- Position the special sealed gasket (provided) on the edge of the cooktop making sure that the ends meet without one lying on top of the other.
- Put the cooktop in the unit opening making sure that it is centred.
- Fasten the hob to the unit with the fastening brackets. The traction of the screws will be enough to cut the sealing gasket so that the excess can easily be removed.

