

ODOUR FILTER COMPATIBILITY CHART FOR IAG RANGEHOODS & CANOPIES

CODE	CARBON FILTER CODES						NUMBER REQUIRED
	IXFC1	IXFC2	IXFC3	IXFC4	XFC5	IXFC6	
RANGEHOOD							
IRS6WE1	■						1
IRS6SE1	■						1
IRO6WE1		■					1
IRO6SE1		■					1
IRO6WE2		■					1
IRO6SE2		■					1
IRO9WE1		■					1
IRO9SE1		■					1
IRO9WE2			■				2
IRO9SE2			■				2
IRI9WE1				■			2
CANOPY							
CODE							
IAS6SE1					■		2
IAS9SE1					■		2
IAG9SE2+						■	1
IAI9SE4 +						■	1
IAF9SE1				■			2

Active Carbon Filter – fitted to motor grill

The active carbon filter filters and dissolves cooking odours. These active carbon filters are not washable nor are they regenerative. Washing of the filter renders the active carbon ineffectual.

The carbon filters should be changed every 3 to 4 months in normal use

+Charcoal Filter – mattress

These charcoal filters can be washed once every two months when used on average 2.5 hours per day. On the IAG9SE2 canopy they should be washed every time the LED 5 marked C starts to flash. Wash using hot water and a suitable detergent, or in a dishwasher at 65C (if dishwasher is used, select full cycle function leaving out dishes)

Eliminate excess water without damaging filter; remove mattress located inside plastic frame. Place in oven for 10 minutes at 100C to dry completely.

Replace the mattress every 3 years or when the cloth is damaged.

IAG9SE2 canopy

Once charcoal filter has been replaced, press button 1 for about 3 seconds until you hear the acoustic signal (beep) LED 5 will stop flashing.

Note:

Carbon / charcoal filters are not required when rangehood or canopies are ducted externally but only when they are in recirculation mode.